

# Series GX15 Pneumatic Pump



## PUMP CATEGORY

Type: Plunger  
Control: Cycle Speed  
Stroke: 1 in (25 mm) Fixed

## FLOW RATE

0.04 - 1.46 USG/H (0.15 - 5.53 L/H)

## PRESSURE

0 - 3,500 PSIG (0 - 241.32 BARG)

## SUPERIOR DESIGN

- Durable, High-Quality Materials
- No Springs or Diaphragms
- Accurate and Repeatable Injection
- Quick Maintenance and Low Downtime
- Optimized for Shale Oil and Gas Production
- High Return on Investment

## CHEMICAL RESISTANCE

Proprietary, high-quality seal materials enable CheckPoint pumps to provide unparalleled chemical resistance. Wetted components are available in an array of materials. Chemical applications include, but are not limited to:

- Scavengers (H<sub>2</sub>S, O<sub>2</sub>, CO<sub>2</sub>)
- Hydrate Inhibitors (MeOH, MEG, LDHI)
- Foamers and Defoamers
- Corrosion, Scale, and Paraffin Inhibitors
- Clarifiers, Biocides, Bleaches, and Acids

## ZERO EMISSIONS

CheckPoint offers standard integrated gas recovery capable of 120 PSIG (8.3 BARG) exhaust backpressure.

## WARRANTY

CheckPoint guarantees 40 months of material and workmanship.

MODEL	FLOW RATE (MINIMUM) USG/H (L/H)	FLOW RATE (MAXIMUM) USG/H (L/H)	WORKING PRESSURE (MAXIMUM) PSIG (BARG)	PISTON DIAMETER IN (MM)	PLUNGER DIAMETER IN (MM)	DIMENSIONS L X W X H IN (MM)	WEIGHT LB (KG)	SUCTION CONNECTION	DISCHARGE CONNECTION
GX15 1/4"	0.04 (0.15)	1.46 (5.53)	3,500 (241.32)	1.5 (38.10)	1/4 (6.35)	4.75 (121) X 5.47 (139) X 10.6 (269)	8.05 (3.65)	1/4" MNPT	1/4" MNPT

Tabular data should be used for quick reference only. See performance curves for accurate pump selection.



www.cppumps.com • sales@cppumps.com

