

Series ATP Single Drive Order Guide



Build Part Number

A	T	P	3	5	6	7	-	9	10	11	12	13	14
-	16	17	18	19	20	21							

A complete Series ATP part number is 14 or 21 digits depending on selected options. For example, ATP11DL-A308RH or ATP12CL-A306RQ-A304RF. Note that some codes are multiple digits.

DIGIT	CODE	SERIES DRIVE TYPE
1-2	AT	ADJUSTABLE TRAVEL

DIGIT	CODE	HEAD TECHNOLOGY
3	P	PLUNGER

DIGIT	CODE	DRIVE STYLE
4	1	STYLE 1 - <i>*DISCONTINUED*</i>
	3	STYLE 3 - EXTERNAL STROKE LENGTH ADJ.

DIGIT	CODE	NUMBER OF HEADS
5	1	1 HEAD
	2	2 HEADS

DIGIT	CODE	MOTOR
6	C	12VDC, VARIABLE SPEED 6-67 RPM, Ta 40°C, 0.20HP, 150 LB-IN, C1D2, 30FT #12/2C, QUICK CONNECTS*, IP65, 9 O'CLOCK SHAFT FOR MANUAL HAND CONTROL
	D	12VDC, VARIABLE SPEED 6-67 RPM, Ta 40°C, 0.20HP, 150 LB-IN, C1D2, 10FT #14/7C, FLYING LEADS IP65, 9 O'CLOCK SHAFT FOR AUTOMATED CONTROL
	J	115VAC/1PH/60HZ, SINGLE SPEED, 60 RPM, Ta 40°C, 0.14HP, 150 LB-IN, C1D2, NO CABLE INCLUDED 9 O'CLOCK SHAFT FOR MANUAL HAND CONTROL
	K	115VAC/1PH/60HZ, SINGLE SPEED, 60 RPM, Ta 40°C, 0.14HP, 150 LB-IN, C1D2, 30FT #14/3C NEMA PLUG* 9 O'CLOCK SHAFT FOR MANUAL HAND CONTROL

* Quick connect or plug end is unclassified and must be installed in a safe zone.

DIGIT	CODE	MOUNT
7	L	LEGS, 20" HEIGHT
	S	FLOOR STAND

PUMP HEAD 1 CONFIGURATION

DIGIT	CODE	HEAD STYLE
9	A	STYLE A

DIGIT	CODE	HEAD / CHECK BODY MATERIAL
10	3	S316

DIGIT	CODE	PLUNGER DIAMETER
11-12	04	1/4"
	06	3/8"
	08	1/2"

DIGIT	CODE	PLUNGER MATERIAL
13	Y	CERAMIC

DIGIT	CODE	WETTED SEAL MATERIAL
14	F	FFKM
	H	HNBR
	Q	FKM

If pump configuration is single head, stop part number here.

PUMP HEAD 2 CONFIGURATION

Only continue if pump configuration is dual head.

DIGIT	CODE	HEAD STYLE
16	A	STYLE A

DIGIT	CODE	HEAD / CHECK BODY MATERIAL
17	3	S316

DIGIT	CODE	PLUNGER DIAMETER
18-19	04	1/4"
	06	3/8"
	08	1/2"

DIGIT	CODE	PLUNGER MATERIAL
20	Y	CERAMIC

DIGIT	CODE	WETTED SEAL MATERIAL
21	F	FFKM
	H	HNBR
	Q	FKM




Series ATP3 Parts Order Guide



PART#	DESCRIPTION
KIT MISCELLANEOUS	
ATP1KBA-A3	KIT BLEED ASSY - BLEED SCREW, SPRING, BALL
ATP1KLA-A3	KIT LEG ASSY - 1 x LEG, 2 X BOLTS, 2 X NUTS
ATPMIT-01	MOTOR INSTALLATION TOOL
KIT HEAD CONVERSION: KATHCK##Y3# (PUMP ORDER GUIDE DIGIT 9-14)	
KATHCK04Y3F	ATP3 HEAD CONVERSION KIT - 1/4 IN - CER PLG - FFKM SEALS - INCLUDES: 316SS GLAND NUT/SLEEVE - CER PLUNGER - NON-ADJUSTABLE SEAL
KATHCK04Y3H	ATP3 HEAD CONVERSION KIT - 1/4 IN - CER PLG - HNBR SEALS - INCLUDES: 316SS GLAND NUT/SLEEVE - CER PLUNGER - NON-ADJUSTABLE SEAL
KATHCK04Y3Q	ATP3 HEAD CONVERSION KIT - 1/4 IN - CER PLG - FFKM SEALS - INCLUDES: 316SS GLAND NUT/SLEEVE - CER PLUNGER - NON-ADJUSTABLE SEAL
KATHCK06Y3F	ATP3 HEAD CONVERSION KIT - 3/8 IN - CER PLG - FFKM SEALS - INCLUDES: 316SS GLAND NUT/SLEEVE - CER PLUNGER - NON-ADJUSTABLE SEAL
KATHCK06Y3H	ATP3 HEAD CONVERSION KIT - 3/8 IN - CER PLG - HNBR SEALS - INCLUDES: 316SS GLAND NUT/SLEEVE - CER PLUNGER - NON-ADJUSTABLE SEAL
KATHCK06Y3Q	ATP3 HEAD CONVERSION KIT - 3/8 IN - CER PLG - FFKM SEALS - INCLUDES: 316SS GLAND NUT/SLEEVE - CER PLUNGER - NON-ADJUSTABLE SEAL
KATHCK08Y3F	ATP3 HEAD CONVERSION KIT - 1/2 IN - CER PLG - FFKM SEALS - INCLUDES: 316SS GLAND NUT - CER PLUNGER - NON-ADJUSTABLE SEAL
KATHCK08Y3H	ATP3 HEAD CONVERSION KIT - 1/2 IN - CER PLG - HNBR SEALS - INCLUDES: 316SS GLAND NUT - CER PLUNGER - NON-ADJUSTABLE SEAL
KATHCK08Y3Q	ATP3 HEAD CONVERSION KIT - 1/2 IN - CER PLG - FFKM SEALS - INCLUDES: 316SS GLAND NUT - CER PLUNGER - NON-ADJUSTABLE SEAL
KIT ADD SECOND HEAD: KATSHK##Y3# (PUMP ORDER GUIDE DIGIT 9-14)	
KATSHK04Y3F	ATP3 ADD SECOND HEAD KIT - 1/4 IN 316SS HEAD - CER PLUNGER - FFKM SEALS - ADJUSTMENT ASSEMBLY
KATSHK04Y3H	ATP3 ADD SECOND HEAD KIT - 1/4 IN 316SS HEAD - CER PLUNGER - HNBR SEALS - ADJUSTMENT ASSEMBLY
KATSHK04Y3Q	ATP3 ADD SECOND HEAD KIT - 1/4 IN 316SS HEAD - CER PLUNGER - FFKM SEALS - ADJUSTMENT ASSEMBLY
KATSHK06Y3F	ATP3 ADD SECOND HEAD KIT - 3/8 IN 316SS HEAD - CER PLUNGER - FFKM SEALS - ADJUSTMENT ASSEMBLY
KATSHK06Y3H	ATP3 ADD SECOND HEAD KIT - 3/8 IN 316SS HEAD - CER PLUNGER - HNBR SEALS - ADJUSTMENT ASSEMBLY
KATSHK06Y3Q	ATP3 ADD SECOND HEAD KIT - 3/8 IN 316SS HEAD - CER PLUNGER - FFKM SEALS - ADJUSTMENT ASSEMBLY
KATSHK08Y3F	ATP3 ADD SECOND HEAD KIT - 1/2 IN 316SS HEAD - CER PLUNGER - FFKM SEALS - ADJUSTMENT ASSEMBLY
KATSHK08Y3H	ATP3 ADD SECOND HEAD KIT - 1/2 IN 316SS HEAD - CER PLUNGER - HNBR SEALS - ADJUSTMENT ASSEMBLY
KATSHK08Y3Q	ATP3 ADD SECOND HEAD KIT - 1/2 IN 316SS HEAD - CER PLUNGER - FFKM SEALS - ADJUSTMENT ASSEMBLY
KIT HEAD REBUILD: KATHRK##N# (PUMP ORDER GUIDE DIGIT 9,11-12,14)	
KATHRK04NF	ATP3 HEAD REBUILD KIT - 1/4 IN - FFKM - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KATHRK04NH	ATP3 HEAD REBUILD KIT - 1/4 IN - HNBR - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KATHRK04NQ	ATP3 HEAD REBUILD KIT - 1/4 IN - FKM - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KATHRK06NF	ATP3 HEAD REBUILD KIT - 3/8 IN - FFKM - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KATHRK06NH	ATP3 HEAD REBUILD KIT - 3/8 IN - HNBR - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KATHRK06NQ	ATP3 HEAD REBUILD KIT - 3/8 IN - FKM - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KATHRK08NF	ATP3 HEAD REBUILD KIT - 1/2 IN - FFKM - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KATHRK08NH	ATP3 HEAD REBUILD KIT - 1/2 IN - HNBR - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KATHRK08NQ	ATP3 HEAD REBUILD KIT - 1/2 IN - FKM - INCLUDES: PLUNGER SEAL KIT, CHECK KITS
KIT PLUNGER: KATPLRU## (PUMP ORDER GUIDE DIGIT 11-13)	
KATPLRCU04	1/4 PLUNGER REPL KIT - CERAMIC
KATPLRCU06	3/8 PLUNGER REPL KIT - CERAMIC
KATPLRCU08	1/2 PLUNGER REPL KIT - CERAMIC
SUCTION AND DISCHARGE CHECK VALVE (PUMP ORDER GUIDE DIGIT 14)	
CFM04S6-B00	CHECK VALVE ASSY - 1/4 MNPT - 1PC FAILSAFE BALL CHECK - CERAMIC BALL - 1 PSIG SPRING - 316SS - 1250/ATP
KIT SUCTION AND DISCHARGE CHECK VALVE REBUILD (PUMP ORDER GUIDE DIGIT 14)	
KFM04S6-B00	KIT SUCTION CHECK REBUILD, CERAMIC BALL, VITON O-RING, SPRING

Series ATP3 Parts Order Guide



PART#	DESCRIPTION
MOTOR (CORRESPONDS TO PUMP ORDER GUIDE DIGIT 6)	
SOLR0009-307M	OPT C: 12VDC, VARIABLE SPEED, 6-67 RPM, Ta 40C, 0.20HP, 150 LB-IN, C1D2, 30FT #12/2C, UNCLASSIFIED QUICK CONNECTS, IP65, 9 O'CLOCK SHAFT, FOR MANUAL HAND CONTROL
SOLR0009-307A	OPT D: 12VDC, VARIABLE SPEED 6-67 RPM, Ta 40C, 0.20HP, 150 LB-IN, C1D2, 10FT #14/7C, FLYING LEADS, IP65, 9 O'CLOCK SHAFT, FOR AUTOMATED CONTROL
EMACFS115V60H1P0020-01	OPT J: 115VAC/1PH/60HZ, SINGLE SPEED, 60 RPM, Ta 40C, 0.14HP, 150 LB-IN, C1D2, NO CABLE INCLUDED, 9 O'CLOCK SHAFT, FOR MANUAL HAND CONTROL
EMACFS115V60H1P0020-02	OPT K: 115VAC/1PH/60HZ, SINGLE SPEED, 60 RPM, Ta 40C, 0.14HP, 150 LB-IN, C1D2, 30FT #14/3C UNCLASSIFIED NEMA PLUG, 9 O'CLOCK SHAFT, FOR MANUAL HAND CONTROL